

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

UV-IPC245LP-ADF60KC-WP

Uniview



Features

- Uniview
- IP Bullet Camera - Easy Range
- 5 MP (2880x1620)
- 6 mm Lens
- Minimum illumination 0.0003 lux | 0 Lux with supplemental lighting
- White light range 50m
- 7 white light bulbs (5 as supplementary light + 2 for warning purposes)
- ColorHunter with Wise-ISP technology: with Uniview's Wise-ISP technology, your images will reach an exceptional level of perfection. This intelligent processor optimizes each frame by reducing noise, improving dynamic range and adjusting colors to deliver superior visual quality. Designed for scenarios with varying light conditions, Wise-ISP guarantees sharp and consistent images, becoming the basis for Uniview's most advanced solutions
- SIP (Smart Intrusion Prevention) Lite: combines artificial intelligence algorithms with real-time video analysis to accurately identify human intrusions, minimizing false alarms caused by animal movements or weather conditions
- UMD (Ultra Motion Detection): thanks to its advanced AI algorithm, UMD is able to detect changes in the environment extremely efficiently, even in conditions of high speed or motion difficult to capture by other technologies
- WDR 120dB
- Integrated microphone
- Integrated speaker
- Alarm 1 Input / 1 Output
- Audio 1 Input / 1 Output
- Slot for microSD up to 512 GB
- Corridor mode 9:16
- PoE
- IP67
- Graphene and plastic



• ONVIF Compatible

Specifications

Brand	Uniview
Range	Easy Project
Image sensor	1/1.8" Progressive Scan CMOS
Maximum resolution	5 Megapixel (2880x1620)
Angle of view (FoV)	88.2° (H), 47.6° (V), 104.0° (D)
Range performance	62.1 m (D), 24.8 m (O), 12.4 m (R), 6.2 m (I)
Main Stream rate	5MP (2880*1620)@25fps; 4MP (2560*1440)@25fps; 3MP (2304*1296)@25fps; 2MP (1920*1080)@30fps; 720P (1280*720)@30fps
Extra Stream rate	640*360@30fps; 2CIF(704*288)@30fps; CIF(352*288)@30fps;
Compression	Ultra 265 / H.265 / H.264 / MJPEG
Lens	6 mm
Minimum illumination	Colour: 0.0003 lux (F1.0, AGC ON)
White light control	Auto / Manual
White light range	50 m
Image improvements	WDR (120dB), BLC, HLC, AGC, 2D/3D-NR, ROI, Privacy Mask, Smart Lighting
Intelligent functions	Motion Detection, Audio Detection, Tamper Protection, Ultra Motion Detection (UMD)
SIP (Smart Intrusion Prevention)	Intelligent Intrusion Prevention. Accurate detection of humans and vehicles to avoid false alarms. Event due to line crossing and intrusion in area
Internal memory	MicroSD Card, Max 512GB
Video Backup	ANR video recovery technology by installing a Micro SD card
Audio	Built-in microphone and speaker
I/O alarms	1/1
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (UNV-Link / UNV-Link Pro)
Interoperability	ONVIF
Power	DC 12V / 7W PoE IEEE802.3af

Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67 Surge protection 4KV
Dimensions	255(Fo) x 125(An) x 102(Al) mm
Weight	870 g
Material	Graphene and plastic